

# MULTI SPLIT

## QIRA wall-mounted air Conditioners

NEW

### TEMPERATURE SETPOINT from 16 to 30°C



#### Ionizer

The ionizer improves air quality in the room. Electrical equipment generates positive ions, also referred to as electro smog, that attract dust and viruses. Negative ions are generated by the ionizer neutralize the charge of positive ions by causing the contaminants to fall on the floor, while reducing the risk of allergy and various infections. The ionizer also helps neutralizing the odors in the room.



#### Wi-Fi control

The Wi-Fi control in standard enables controlling the air conditioner with your smartphone connected to the Internet from any place. The comfortable and intuitive Wi-Fi INTELLIGENT AIR app enables access to all basic settings of the air conditioner.



#### High energy efficiency

Innovative solutions enabled a significant reduction of energy consumption in both cooling and heating mode. The appliances have A++/A+ energy rating.



#### SMART airflow

An innovative solution for airflow control. The stream is directed upwards during the cooling and downwards during the heating, which enables an even distribution of air, thus preventing direct airflow on the user.



#### Airflow speed control

The option to control airflow shutters vertically and horizontally enables precise direction of the airflow. The up-down and left-right control functions are available from the wireless controller and the Wi-Fi Intelligent Air app.





Indoor unit



Wireless controller  
YR-HAC01  
(included)

Indoor unit			JS025-QW2	JS035-QW2	JS050-QW2
Rated capacity	Cooling	kW	2,6	3,5	5,0
	Heating	kW	2,8	3,5	5,2
Electrical parameters	Power supply	f/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50
Performance	Airflow	m <sup>3</sup> /h	550	600	900
	Sound power level	dB(A)	54	56	57
	Sound pressure level	dB(A)	37/32/28/18	37/33/29/19	44/40/35/28
Installation	Dimensions without packaging (W/D/H)	mm	805/200/290	805/200/290	975/220/320
	Dimensions with packaging (W/D/H)	mm	874/270/363	874/270/363	1050/301/397
	Net/gross weight	kg	8.3/10.5	8.3/10.5	11.6/14.4
	Liquid pipe diameter	mm	6,35	6,35	6,35
	Gas pipe diameter	mm	9,52	9,52	12,7
	Controller	Standard	YR-HAC01	YR-HAC01	YR-HAC01