


SPLIT

CASSETTE air conditioners


with round-way airflow

Heiko cassette air conditioners are a great solution for installation in the home, office, or restaurant. The range includes units with different capacities to match the size of the building area. The cassette air conditioners are available with a perimeter airflow panel. Heiko units are unobtrusive, installation-friendly and will blend in well with any décor.


TEMPERATURE SETPOINT from 16 to 30°C



Round-way
airflow



High energy
efficiency



SMART
airflow



Airflow
control



Quiet
operation

TURBO MODE

ONE-TOUCH
FULL POWER

**SLEEP
FUNCTION**

SLEEP FUNCTION
MAKE YOUR SLEEP
COMFORTABLE

**AUTO
COOLING
HEATING
DRYING
FAN**



Indoor unit




Cover
PB-950HE4
(option)



Wireless controller
YR-NRS01
(option)



Wired controller
YR-C01
(option)



Outdoor unit

Indoor unit				CA070-A1	CA100-A1
Outdoor unit				JZ070-A1	JZ100-A1
Rated value	Capacity	– Cooling	Btu/h (nom.)	22200	31400
			kW nom. (min.~max)	7.1 (2-7.3)	9.2 (2.5-10.0)
		– Heating	Btu/h (nom.)	24300	34800
			kW nom. (min. – max)	8.0 (2.5-8)	10.2 (3.0-10.5)
	Power input	– Cooling	kW nom. (min. ~ max)	2.20 (0.5-2.6)	3.12 (0.5-4.0)
		– Heating	kW nom. (min. ~ max)	1.91 (0.5-2.6)	2.91 (0.5-4.0)
	EER/COP			3.23/3.72	3/3.5
Season value	SEER/SCOP			6.1/3.8	5.9/3.8
	Energy rating (cooling/heating)			A++/A	A+/A
	Annual energy consumption (cooling)		kWh	406	555
	Annual energy consumption (heating)		kWh	1831	2780
Indoor unit				CA070-A1	CA100-A1
Electrical parameters	Power supply		f/V/Hz	1/220-240/50/60	1/220-240/50/60
Performance	Airflow		m³/h	1260/1070/820/680	1680/1530/1320/1190
	Sound power level		dB(A)	55	62
	Sound pressure level		dB(A)	42/40/38/35	45/42/38/34
Installation	Package dimensions (W/D/H)		mm	840/840/204	840/840/246
	Dimensions with packaging (W/D/H)		mm	990/990/310	990/990/310
	Net/gross weight		kg	27/32	31/36
	Controller		wireless option	YR-NRS01	YR-NRS01
			wired option	YR-C01	YR-C01
Cover	Model		option	PB-950HE4	PB-950HE4
	Dimensions (W/D/H)		mm	950/950/50	950/950/50
	Dimensions with packaging (W/D/H)		mm	1000/1000/110	1000/1000/110
	Net/gross weight		kg	6.5/9	6.5/9
Outdoor unit				JZ070-A1	JZ100-A1
Electrical parameters	Power supply		f/V/Hz	1/220–240/50/60	1/220–240/50/60
Performance	Airflow (H)		m³/h	3000	3500
	Sound power level		dB(A)	67	66
	Sound pressure level		dB(A)	54	53
Montaż	Package dimensions (W/D/H)		mm	890/353/697	920/372/760
	Dimensions with packaging (W/D/H)		mm	1046/460/780	1036/478/820
	Net/gross weight		kg	48/53	60/65
	Compressor type			Twin rotary	Twin rotary
	Refrigerant			R32	R32
	GWP			675	675
	Liquid pipe diameter		mm	9.52	9.52
	Gas pipe diameter		mm	15.88	15.88
	Total pipeline length (max)		m	50	50
	Max level difference		m	30	30
	Refrigerant filling		kg	1.3	1.5
	Total pipeline length without refill		m	10	30
	Extra refrigerant per metre of pipeline		g/m	45	45
Warunki robocze (zewn.)	Cooling (min. - max.)		°C	-10~46	-10~46
	Heating (min. - max.)		°C	-15~24	-15~24