NEW!

# C-DUCT Slim duct units

Colour
White matt (cover)

**Temperature setpoint from 16 to 30°C**

The HEIKO C-DUCT | Slim duct unit, designed for MULTI SPLIT operation, is a solution created for discreet and efficient air conditioning of commercial spaces. The slim design allows installation in narrow ceiling spaces, while the inverter technology, high energy efficiency and quiet operation guarantee stable operation and even air distribution throughout the building.

- High energy efficiency
- SMART airflow
- Airflow control
- 5 operating modes
- Inverter technology
- Automatic defrosting
- DC motor
- Hydrophilic aluminium foil
- Silent operation

Indoor unit

Cover (optional)

**P1B-890-A1S or P1B-1210-A1S**

Wireless controller (option)

**YR-NRS01**

Wired controller (option)

**YR-C01**

## C-DUCT DUCT UNITS | SLIM

| INDOOR UNIT | | | DU035-A1S | DU050-A1S |
|---|---|---|---|---|
| Rated capacity | Cooling | KW | 3.5 | 5.0 |
| | Heating | KW | 4.0 | 5.5 |
| Electrical rating | Power supply | Ph/V/Hz | 1/220-240/50/60 | 1/220-240/50/60 |
| Performance | Airflow | m3/h | 600/480/420/350 | 900/750/600/450 |
| | Static pressure | pa | 0/10/20/40 | 0/10/20/40 |
| | Sound Power Level | DB(A) | 53 | 54 |
| | Sound pressure level | DB(A) | 33/28/25/23 | 36/34/32/27 |
| Installation | Net dimensions (W/H/D) | mm | 850/420/185 | 1170/420/185 |
| | Gross dimensions (W/H/D) | mm | 1045/530/260 | 1365/530/260 |
| | Net/gross weight | kg | 16/21 | 22/28 |
| | Liquid pipe diameter | mm | 6.35 | 6.35 |
| | Gas pipe diameter | mm | 9.52 | 12.7 |
| | Control unit | Wireless option | YR-NRS01 | YR-NRS01 |
| | | Wired option | YR-C01 | YR-C01 |
| Cover | Type | Option | P1B-890-A1S | P1B-1210-A1S |
| | Net dimensions (W/H/D) | mm | 890/190/100 (outlet) 890/290.5/32.4 (inlet) | 1210/190/100 (outlet) 1210/290.5/32.4 (inlet) |
| | Gross dimensions (W/H/D) | mm | 938/335/220 | 1258/335/220 |
| | Net/gross weight | kg | 4/5 | 5/6 |

**DU035-A1S**




**DU050-A1S**